

RECEIVED
CENTRAL FAX CENTERUS Serial No. 10/087,500
Page 2 of 5

JUL 25 2006

Amendment to the Claims

1. (canceled)
2. (currently amended) ~~The roof rail air bag assembly of claim 1, further comprising~~
A snap-in roof rail air bag assembly for a vehicle having a roof rail, comprising:
an air bag module including an air bag inflator and an air bag with at least one cushion
retention tab:
a snap-in clip permanently attachable to the roof rail and selectively attachable to the at
least one cushion retention tab, said snap-in clip including a fastening portion;
a removable serviceability attachment feature for attaching the air bag module at the at
least one cushion retention tab to the snap-in clip by fastening said serviceability attachment
feature to said fastening portion of said snap-in clip, and for selectively detaching the air bag
module from the snap-in clip for removal of the air bag module for service by removing said
serviceability attachment feature from said fastening portion of said snap-in clip; and
an inflator bracket having an inflator support portion supporting the air bag inflator and
an attachment portion having a mounting tab for receiving the serviceability attachment feature,
and for capturing the at least one cushion retention tab between the inflator bracket and the snap-
in clip.
3. (original) The roof rail air bag assembly of claim 2, further comprising an air bag
cover protectingly covering the air bag, and having a tear seam along one edge.
4. (original) The roof rail air bag assembly of claim 3, wherein the cushion retention
tab extends through the air bag cover, for at least partially supporting the air bag and the air bag
cover.
5. (original) The roof rail air bag assembly of claim 4, wherein the mounting tab of
the inflator bracket is attached to the snap-in clip with the serviceability attachment feature.

US Serial No. 10/087,500
Page 3 of 5

- 6. (canceled)
- 7. (canceled)
- 8. (canceled)

9. (currently amended) ~~The method of claim 8, further comprising~~ A method of installing an air bag module having an air bag inflator and an air bag with at least one cushion retention tab in a vehicle having a roof rail, comprising:

attaching the air bag module to an inflator bracket having an inflator support portion and an attachment portion with a mounting tab;

attaching a snap-in clip having a fastening portion to the at least one cushion retention tab with a removable serviceability attachment feature by fastening said removable serviceability attachment feature to said fastening portion;

capturing the cushion retention tab between the mounting tab and the snap-in clip prior to attaching the snap-in clip to the cushion retention tab; and

installing the air bag module in the vehicle by inserting the snap-in clip into the roof rail.

- 10. (canceled)

11. (currently amended) ~~The roof rail air bag assembly of claim 10, further comprising~~ In combination with a vehicle having a roof rail, a roof rail air bag assembly adapted for snap-in installation in the roof rail of the vehicle, from outside the vehicle, the air bag assembly comprising:

an air bag module including an air bag inflator and an air bag with at least one cushion retention tab;

a snap-in clip permanently attachable to the roof rail and selectively attachable to the at least one cushion retention tab said snap-in clip including a fastening portion;

a removable serviceability attachment feature for attaching the air bag module at the at least one cushion retention tab to the snap-in clip by fastening said serviceability attachment feature to said fastening portion of said snap-in clip, and for selectively detaching the air bag

US Serial No. 10/087,500
Page 4 of 5

module from the snap-in clip for removal of the air bag module for service by removing said serviceability attachment feature from said fastening portion of said snap-in clip; and

an inflator bracket having an inflator support portion connected to the air bag inflator and an attachment portion having a mounting tab for receiving the serviceability attachment feature, and for capturing the at least one cushion retention tab between the inflator bracket and the snap-in clip.